


Technical Specifications VSP SS 10210 Range



- Diffuser** : Stainless steel (AISI 304L) **Max. sand content** : 50 gr / m³
- Impeller** : Stainless steel (AISI 304L) **Valve cap** : Stainless steel
- Pump shaft** : Stainless steel (AISI 420) **Voltage** : 380-415 V (+%6 / -%10)
- Coupling** : Stainless steel (AISI 420) **Frequency** : 50 Hz.
- Strainer** : Stainless steel (AISI 304) **Max. water temperature** : 50°
- Outlet connection diameter** : 5" (inside threaded) **Degree of protection** : IP 68

Pump Model	Stages	Motor		Dimensions(mm)					Weight(kg)		
		kW	HP	L	LM	LP	ΦM	ΦP	Motor	Pump	Total
VSP SS 10210/01	1	18,5	25	1767	973	794	142	247	72	44	116
VSP SS 10210/02	2	37	50	2217/1950/2026	1247/980/1056	970	142/172/192	247	103/103/129	55	158/158/184
VSP SS 10210/03	3	55	75	2365/2433	1218/1286	1147	172/192	247	138/170	66	204/236
VSP SS 10210/04	4	75	100	2689/2573	1366/1250	1323	192/231	247	186/200	76	262/276
VSP SS 10210/05	5	92	125	2970/2869	1471/1370	1499	192/231	247	210/256	87	297/343
VSP SS 10210/06	6	110	150	3276/3105	1601/1430	1675	192/231	247	235/284	98	333/382
VSP SS 10210/07	7	129	175	3361	1510	1851	231	247	311	109	420
VSP SS 10210/08	8	150	200	3638	1610	2028	231	247	338	119	457
VSP SS 10210/09	9	166	225	3944	1740	2204	231	247	370	130	500
VSP SS 10210/10	10	185	250	4200	1820	2380	231	247	400	141	541
VSP SS 10210/11	11	220	300	4376	1820	2556	231	247	405	152	557
VSP SS 10210/12	12	220	300	4552	1820	2732	231	247	405	162	567

